

870 Order Status Report

Functional Group ID=**RS**

Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the Order Status Report Transaction Set (870) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to report on the current status of a requirement forecast, an entire purchase order, selected line items on a purchase order, selected products/services on a purchase order, or purchase orders for a specific customer in their entirety or on a selection basis. The transaction set can also be used to report on the current status of single or multiple requisitions. The report format allows for the inclusion of "reasons" relative to the status. This transaction set may also be used to update the supplier's scheduled shipment or delivery dates. This transaction set can result from either an inquiry or a prearranged schedule agreed to by the trading partners.

Heading:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
M	010	ST	Transaction Set Header	M	1		
M	020	BSR	Beginning Segment for Order Status Report	M	1		
						200	
	050	N1	Name	O	1		

Detail:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
						1000	
M	010	HL	Hierarchical Level	M	1		
	020	PRF	Purchase Order Reference	O	1		
						1000	
	150	PO1	Baseline Item Data	O	1		
	180	PID	Product/Item Description	O	1000		
	190	MEA	Measurements	O	40		
						104	
	210	ISR	Item Status Report	O	1		
	220	PID	Product/Item Description	O	6		
	230	QTY	Quantity	O	4		

Summary:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
M	020	SE	Transaction Set Trailer	M	1		

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Semantic Notes: 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	ST01	143	Transaction Set Identifier Code Code uniquely identifying a Transaction Set	M ID 3/3
M	ST02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9

Segment: **BSR** Beginning Segment for Order Status Report
Position: 020
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the beginning of an Order Status Report Transaction Set
Syntax Notes:
Semantic Notes:

- 1 BSR03 indicates a status report document number assigned by the sender.
- 2 BSR04 indicates the date of this report from the sender.
- 3 BSR07 indicates the time of this report from the sender.
- 4 BSR08 indicates a status report document number assigned by the inquirer.
- 5 BSR09 indicates the date this report was requested from the sender by the inquirer.
- 6 BSR10 indicates the time this report was requested from the sender by the inquirer.

Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	BSR01	850	Status Report Code Code indicating the reason for sending the report 2 Prearranged Schedule or Agreement	M ID 1/2
M	BSR02	847	Order/Item Code Code identifying a group of orders and items CA All Orders - All Items	M ID 1/2
M	BSR03	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M AN 1/30
M	BSR04	373	Date Date expressed as CCYYMMDD	M DT 8/8
	BSR07	337	Time Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	O TM 4/8

Segment: **N1** Name
Position: 050
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: 1
Purpose: To identify a party by type of organization, name, and code
Syntax Notes: 1 At least one of N102 or N103 is required.
 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:
Comments: 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
 2 N105 and N106 further define the type of entity in N101.

Data Element Summary

Ref.	Data Element	Name	Attributes	
			M	ID
M	N101	98 Entity Identifier Code		2/3
		Code identifying an organizational entity, a physical location, property or an individual		
		ST Ship To		
		SU Supplier/Manufacturer		
	N102	93 Name	X	AN 1/60
		Free-form name		
	N103	66 Identification Code Qualifier	X	ID 1/2
		Code designating the system/method of code structure used for Identification Code (67)		
		1 D-U-N-S Number, Dun & Bradstreet		
	N104	67 Identification Code	X	AN 2/80
		Code identifying a party or other code		

Segment: **HL Hierarchical Level**
Position: 010
Loop: HL Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Syntax Notes:

Semantic Notes:

Comments:

- 1 The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
The HL segment defines a top-down/left-right ordered structure.
- 2 HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
- 3 HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
- 4 HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
- 5 HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

Data Element Summary

	<u>Ref.</u>	<u>Data</u>		<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>	<u>Name</u>	
M	HL01	628	Hierarchical ID Number	M AN 1/12
			A unique number assigned by the sender to identify a particular data segment in a hierarchical structure	
M	HL03	735	Hierarchical Level Code	M ID 1/2
			Code defining the characteristic of a level in a hierarchical structure	
			O Order	

Segment: **PRF** Purchase Order Reference
Position: 020
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To provide reference to a specific purchase order
Syntax Notes:
Semantic Notes: 1 PRF04 is the date assigned by the purchaser to purchase order.
Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	PRF01	324	Purchase Order Number Identifying number for Purchase Order assigned by the orderer/purchaser	M AN 1/22
	PRF04	373	Date Date expressed as CCYYMMDD	O DT 8/8
	PRF05	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	O AN 1/20

Segment:	PO1 Baseline Item Data
Position:	150
Loop:	PO1 Optional
Level:	Detail
Usage:	Optional
Max Use:	1
Purpose:	To specify basic and most frequently used line item data
Syntax Notes:	<ol style="list-style-type: none"> 1 If PO103 is present, then PO102 is required. 2 If PO105 is present, then PO104 is required. 3 If either PO106 or PO107 is present, then the other is required. 4 If either PO108 or PO109 is present, then the other is required. 5 If either PO110 or PO111 is present, then the other is required. 6 If either PO112 or PO113 is present, then the other is required. 7 If either PO114 or PO115 is present, then the other is required. 8 If either PO116 or PO117 is present, then the other is required. 9 If either PO118 or PO119 is present, then the other is required. 10 If either PO120 or PO121 is present, then the other is required. 11 If either PO122 or PO123 is present, then the other is required. 12 If either PO124 or PO125 is present, then the other is required.
Semantic Notes:	
Comments:	<ol style="list-style-type: none"> 1 See the Data Element Dictionary for a complete list of IDs. 2 PO101 is the line item identification. 3 PO106 through PO125 provide for ten different product/service IDs per each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Data Element Summary

<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
<u>Des.</u>	<u>Element</u>		
PO102	330	Quantity Ordered Quantity ordered	X R 1/15
PO103	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken LB Pound	O ID 2/2
PO106	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) BP Buyer's Part Number	X ID 2/2
PO107	234	Product/Service ID Identifying number for a product or service	X AN 1/48
PO108	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) VO Vendor's Order Number	X ID 2/2
PO109	234	Product/Service ID Identifying number for a product or service	X AN 1/48
PO110	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) VN Vendor's (Seller's) Item Number	X ID 2/2
PO111	234	Product/Service ID Identifying number for a product or service	X AN 1/48
PO112	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) GC Grade Code	X ID 2/2

PO113

234

Product/Service ID

X AN 1/48

Identifying number for a product or service

Segment: **PID** Product/Item Description

Position: 180

Loop: PO1 Optional

Level: Detail

Usage: Optional

Max Use: 1000

Purpose: To describe a product or process in coded or free-form format

Syntax Notes:

- 1 If PID04 is present, then PID03 is required.
- 2 At least one of PID04 or PID05 is required.
- 3 If PID07 is present, then PID03 is required.
- 4 If PID08 is present, then PID04 is required.
- 5 If PID09 is present, then PID05 is required.

Semantic Notes:

- 1 Use PID03 to indicate the organization that publishes the code list being referred to.
- 2 PID04 should be used for industry-specific product description codes.
- 3 PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
- 4 PID09 is used to identify the language being used in PID05.

Comments:

- 1 If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
- 2 Use PID06 when necessary to refer to the product surface or layer being described in the segment.
- 3 PID07 specifies the individual code list of the agency specified in PID03.

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	PID01	349 Item Description Type Code indicating the format of a description F Free-form	M ID 1/1
	PID02	750 Product/Process Characteristic Code Code identifying the general class of a product or process characteristic 9B Product Application	O ID 2/3
	PID05	352 Description A free-form description to clarify the related data elements and their content	X AN 1/80

Segment: **MEA** Measurements

Position: 190

Loop: PO1 Optional

Level: Detail

Usage: Optional

Max Use: 40

Purpose: To specify physical measurements or counts, including dimensions, tolerances, variances, and weights (See Figures Appendix for example of use of C001)

- Syntax Notes:**
- 1 At least one of MEA03 MEA05 MEA06 or MEA08 is required.
 - 2 If MEA05 is present, then MEA04 is required.
 - 3 If MEA06 is present, then MEA04 is required.
 - 4 If MEA07 is present, then at least one of MEA03 MEA05 or MEA06 is required.
 - 5 Only one of MEA08 or MEA03 may be present.

Semantic Notes: 1 MEA04 defines the unit of measure for MEA03, MEA05, and MEA06.

Comments: 1 When citing dimensional tolerances, any measurement requiring a sign (+ or -), or any measurement where a positive (+) value cannot be assumed, use MEA05 as the negative (-) value and MEA06 as the positive (+) value.

Data Element Summary

<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
<u>Des.</u>	<u>Element</u>		
MEA01	737	Measurement Reference ID Code Code identifying the broad category to which a measurement applies PD Physical Dimensions	O ID 2/2
MEA02	738	Measurement Qualifier Code identifying a specific product or process characteristic to which a measurement applies TH Thickness WD Width	O ID 1/3
MEA03	739	Measurement Value The value of the measurement	X R 1/20
MEA04	C001	Composite Unit of Measure To identify a composite unit of measure (See Figures Appendix for examples of use)	X
M	C00101	355 Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken IN Inch	M ID 2/2

Segment: **ISR** Item Status Report
Position: 210
Loop: ISR Optional
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify detailed purchase order/item status
Syntax Notes:
Semantic Notes: 1 If ISR01 specifies a date, ISR02 is required.
Comments:

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
M	ISR01	368	Shipment/Order Status Code	M ID 2/2
			Code indicating the status of an order or shipment or the disposition of any difference between the quantity ordered and the quantity shipped for a line item or transaction	
			AS Available Now - Scheduled to Ship (date)	
			AU Available to Ship - Unbilled Quantity	
			ED Expect to Ship By (Date)	
			IN In Process	
			PH Product On Hold	
			QN Quantity Net Due	
			SL Shipped - to - Date through (Date)	
			SP Scheduled for Production at Factory on (Date)	
			UN Unavailable	
			ZZ Mutually Defined	
	ISR02	373	Date	O DT 8/8
			Date expressed as CCYYMMDD	

Segment: **PID** **Product/Item Description**

Position: 220

Loop: ISR Optional

Level: Detail

Usage: Optional

Max Use: 6

Purpose: To describe a product or process in coded or free-form format

Syntax Notes:

- 1 If PID04 is present, then PID03 is required.
- 2 At least one of PID04 or PID05 is required.
- 3 If PID07 is present, then PID03 is required.
- 4 If PID08 is present, then PID04 is required.
- 5 If PID09 is present, then PID05 is required.

Semantic Notes:

- 1 Use PID03 to indicate the organization that publishes the code list being referred to.
- 2 PID04 should be used for industry-specific product description codes.
- 3 PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
- 4 PID09 is used to identify the language being used in PID05.

Comments:

- 1 If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
- 2 Use PID06 when necessary to refer to the product surface or layer being described in the segment.
- 3 PID07 specifies the individual code list of the agency specified in PID03.

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	PID01	349 Item Description Type	M ID 1/1
		Code indicating the format of a description	
		S Structured (From Industry Code List)	
	PID02	750 Product/Process Characteristic Code	O ID 2/3
		Code identifying the general class of a product or process characteristic	
		PR Manufacturing Process	
		Production operations performed on the product being reported	
	PID03	559 Agency Qualifier Code	X ID 2/2
		Code identifying the agency assigning the code values	
		ST American Iron & Steel Institute	
	PID04	751 Product Description Code	X AN 1/12
		A code from an industry code list which provides specific data about a product characteristic	
	PID06	752 Surface/Layer/Position Code	O ID 2/2
		Code indicating the product surface, layer or position that is being described	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
	PID07	822 Source Subqualifier	O AN 1/15
		A reference that indicates the table or text maintained by the Source Qualifier	

Segment: QTY Quantity
Position: 230
Loop: ISR Optional
Level: Detail
Usage: Optional
Max Use: 4
Purpose: To specify quantity information
Syntax Notes: 1 At least one of QTY02 or QTY04 is required.
 2 Only one of QTY02 or QTY04 may be present.
Semantic Notes: 1 QTY04 is used when the quantity is non-numeric.
Comments:

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	QTY01	673	Quantity Qualifier Code specifying the type of quantity 01 Discrete Quantity	M ID 2/2
	QTY02	380	Quantity Numeric value of quantity	X R 1/15
	QTY03	C001	Composite Unit of Measure To identify a composite unit of measure (See Figures Appendix for examples of use)	O
M	C00101	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken LB Pound	M ID 2/2

Segment: **SE** Transaction Set Trailer
Position: 020
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Syntax Notes:

Semantic Notes:

Comments: 1 SE is the last segment of each transaction set.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	SE01	96	Number of Included Segments Total number of segments included in a transaction set including ST and SE segments	M N0 1/10
M	SE02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9