

850 Purchase Order

Functional Group ID=**PO**

Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the Purchase Order Transaction Set (850) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to the placement of purchase orders for goods and services. This transaction set should not be used to convey purchase order changes or purchase order acknowledgment information.

Heading:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
M	010	ST	Transaction Set Header	M	1		
M	020	BEG	Beginning Segment for Purchase Order	M	1		
	050	REF	Reference Identification	O	>1		
	060	PER	Administrative Communications Contact	O	3		
	080	FOB	F.O.B. Related Instructions	O	>1		
	150	DTM	Date/Time Reference	O	10		
	190	PID	Product/Item Description	O	200		
	200	MEA	Measurements	O	40		
	220	PKG	Marking, Packaging, Loading	O	200		
LOOP ID - N1						200	
	310	N1	Name	O	1		
	330	N3	Address Information	O	2		
	340	N4	Geographic Location	O	>1		

Detail:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
LOOP ID - PO1						100000	
M	010	PO1	Baseline Item Data	M	1		n1
	015	LIN	Item Identification	O	>1		
LOOP ID - CTP						>1	
	040	CTP	Pricing Information	O	1		
	049	MEA	Measurements	O	40		
LOOP ID - PID						1000	
	050	PID	Product/Item Description	O	1		
	100	REF	Reference Identification	O	>1		
	210	DTM	Date/Time Reference	O	10		
LOOP ID - SCH						200	
	295	SCH	Line Item Schedule	O	1		n2

Summary:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
LOOP ID - CTT						1	

	010	CTT	Transaction Totals	O	1	n3
M	030	SE	Transaction Set Trailer	M	1	

Transaction Set Notes

1. PO102 is required.
2. The SCH segment is used to specify various quantities of items ordered that are to be scheduled. When this segment is used the unit of measurement code (SCH02) should always be identical to the unit of measurement code in the associated PO1 segment (PO103) and the sum of values of quantity (SCH01) should always equal the quantity ordered (PO102) in the PO1 segment.
3. The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Semantic Notes: 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	ST01	143	Transaction Set Identifier Code Code uniquely identifying a Transaction Set 850 Purchase Order	M ID 3/3
M	ST02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9

Segment: **BEG** Beginning Segment for Purchase Order
Position: 020
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the beginning of the Purchase Order Transaction Set and transmit identifying numbers and dates

Syntax Notes:
Semantic Notes: 1 BEG05 is the date assigned by the purchaser to purchase order.
Comments:

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	BEG01	353	Transaction Set Purpose Code Code identifying purpose of transaction set 00 Original	M ID 2/2
M	BEG02	92	Purchase Order Type Code Code specifying the type of Purchase Order TC Toll Conversion Order	M ID 2/2
M	BEG03	324	Purchase Order Number Identifying number for Purchase Order assigned by the orderer/purchaser	M AN 1/22
M	BEG05	373	Date Date expressed as CCYYMMDD	M DT 8/8
	BEG06	367	Contract Number Contract number	O AN 1/30

Segment: **REF** Reference Identification
Position: 050
Loop:
Level: Heading
Usage: Optional
Max Use: >1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	REF01	128	Reference Identification Qualifier	M ID 2/3
			Code qualifying the Reference Identification	
			C1 Customer material specification number	
			C3 Customer specification number	
			ZZ Mutually Defined	
	REF02	127	Reference Identification	X AN 1/30
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	

Segment: **PER** Administrative Communications Contact
Position: 060
Loop:
Level: Heading
Usage: Optional
Max Use: 3
Purpose: To identify a person or office to whom administrative communications should be directed
Syntax Notes:

- 1 If either PER03 or PER04 is present, then the other is required.
- 2 If either PER05 or PER06 is present, then the other is required.
- 3 If either PER07 or PER08 is present, then the other is required.

Semantic Notes:
Comments:

Data Element Summary

M	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
	PER01	366	Contact Function Code Code identifying the major duty or responsibility of the person or group named Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 2/2
	PER02	93	Name Free-form name	O AN 1/60
	PER03	365	Communication Number Qualifier Code identifying the type of communication number FX Facsimile TE Telephone	X ID 2/2
	PER04	364	Communication Number Complete communications number including country or area code when applicable	X AN 1/80
	PER05	365	Communication Number Qualifier Code identifying the type of communication number FX Facsimile	X ID 2/2
	PER06	364	Communication Number Complete communications number including country or area code when applicable	X AN 1/80
	PER07	365	Communication Number Qualifier Code identifying the type of communication number Refer to 004010 Data Element Dictionary for acceptable code values.	X ID 2/2
	PER08	364	Communication Number Complete communications number including country or area code when applicable	X AN 1/80
	PER09	443	Contact Inquiry Reference Additional reference number or description to clarify a contact number	O AN 1/20

Segment: **FOB** F.O.B. Related Instructions
Position: 080
Loop:
Level: Heading
Usage: Optional
Max Use: >1
Purpose: To specify transportation instructions relating to shipment
Syntax Notes:

- 1 If FOB03 is present, then FOB02 is required.
- 2 If FOB04 is present, then FOB05 is required.
- 3 If FOB07 is present, then FOB06 is required.
- 4 If FOB08 is present, then FOB09 is required.

Semantic Notes:

- 1 FOB01 indicates which party will pay the carrier.
- 2 FOB02 is the code specifying transportation responsibility location.
- 3 FOB06 is the code specifying the title passage location.
- 4 FOB08 is the code specifying the point at which the risk of loss transfers. This may be different than the location specified in FOB02/FOB03 and FOB06/FOB07.

Comments:

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	FOB01	146 Shipment Method of Payment	M ID 2/2
		Code identifying payment terms for transportation charges	
		CC Collect	

Segment: **DTM** Date/Time Reference
Position: 150
Loop:
Level: Heading
Usage: Optional
Max Use: 10
Purpose: To specify pertinent dates and times
Syntax Notes:

- 1 At least one of DTM02 DTM03 or DTM05 is required.
- 2 If DTM04 is present, then DTM03 is required.
- 3 If either DTM05 or DTM06 is present, then the other is required.

Semantic Notes:
Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	DTM01	374	Date/Time Qualifier Code specifying type of date or time, or both date and time 007 Effective	M ID 3/3
	DTM02	373	Date Date expressed as CCYYMMDD	X DT 8/8
	DTM03	337	Time Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	X TM 4/8

Segment: **PID** Product/Item Description
Position: 190
Loop:
Level: Heading
Usage: Optional
Max Use: 200
Purpose: To describe a product or process in coded or free-form format
Syntax Notes:

- 1 If PID04 is present, then PID03 is required.
- 2 At least one of PID04 or PID05 is required.
- 3 If PID07 is present, then PID03 is required.
- 4 If PID08 is present, then PID04 is required.
- 5 If PID09 is present, then PID05 is required.

Semantic Notes:

- 1 Use PID03 to indicate the organization that publishes the code list being referred to.
- 2 PID04 should be used for industry-specific product description codes.
- 3 PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
- 4 PID09 is used to identify the language being used in PID05.

Comments:

- 1 If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
- 2 Use PID06 when necessary to refer to the product surface or layer being described in the segment.
- 3 PID07 specifies the individual code list of the agency specified in PID03.

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	PID01	349 Item Description Type Code indicating the format of a description F Free-form S Structured (From Industry Code List)	M ID 1/1
	PID03	559 Agency Qualifier Code Code identifying the agency assigning the code values ST American Iron & Steel Institute	X ID 2/2
	PID04	751 Product Description Code A code from an industry code list which provides specific data about a product characteristic	X AN 1/12
	PID05	352 Description A free-form description to clarify the related data elements and their content	X AN 1/80
	PID07	822 Source Subqualifier A reference that indicates the table or text maintained by the Source Qualifier	O AN 1/15

Segment: **MEA** Measurements
Position: 200
Loop:
Level: Heading
Usage: Optional
Max Use: 40
Purpose: To specify physical measurements or counts, including dimensions, tolerances, variances, and weights (See Figures Appendix for example of use of C001)
Syntax Notes:

- 1 At least one of MEA03 MEA05 MEA06 or MEA08 is required.
- 2 If MEA05 is present, then MEA04 is required.
- 3 If MEA06 is present, then MEA04 is required.
- 4 If MEA07 is present, then at least one of MEA03 MEA05 or MEA06 is required.
- 5 Only one of MEA08 or MEA03 may be present.

Semantic Notes:

- 1 MEA04 defines the unit of measure for MEA03, MEA05, and MEA06.

Comments:

- 1 When citing dimensional tolerances, any measurement requiring a sign (+ or -), or any measurement where a positive (+) value cannot be assumed, use MEA05 as the negative (-) value and MEA06 as the positive (+) value.

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>		
MEA01	737	Measurement Reference ID Code	O ID 2/2
		Code identifying the broad category to which a measurement applies	
		OD Ordered Dimensions	
		SD Shipped Dimensions	
		WT Weights	
MEA02	738	Measurement Qualifier	O ID 1/3
		Code identifying a specific product or process characteristic to which a measurement applies	
		ID Inside Diameter	
		LN Length	
		OD Outside Diameter	
		TH Thickness	
		WD Width	
		WT Weight	
MEA03	739	Measurement Value	X R 1/20
		The value of the measurement	
MEA04	C001	Composite Unit of Measure	X
		To identify a composite unit of measure (See Figures Appendix for examples of use)	
M	C00101	Unit or Basis for Measurement Code	M ID 2/2
		Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
		ED Inches, Decimal--Nominal	
		EM Inches, Decimal-Minimum	
		IN Inch	
		KG Kilogram	
		LB Pound	
		LM Linear Meter	
		MB Millimeter-Nominal	
		MM Millimeter	
		MZ Millimeter-minimum	
MEA05	740	Range Minimum	X R 1/20
		The value specifying the minimum of the measurement range	

MEA06

741

Range Maximum

X R 1/20

The value specifying the maximum of the measurement range

Segment: **PKG** Marking, Packaging, Loading
Position: 220
Loop:
Level: Heading
Usage: Optional
Max Use: 200
Purpose: To describe marking, packaging, loading, and unloading requirements
Syntax Notes:

- 1 At least one of PKG04 PKG05 or PKG06 is required.
- 2 If PKG04 is present, then PKG03 is required.
- 3 If PKG05 is present, then PKG01 is required.

Semantic Notes:

- 1 PKG04 should be used for industry-specific packaging description codes.

Comments:

- 1 Use the MEA (Measurements) Segment to define dimensions, tolerances, weights, counts, physical restrictions, etc.
- 2 If PKG01 equals "F", then PKG05 is used. If PKG01 equals "S", then PKG04 is used. If PKG01 equals "X", then both PKG04 and PKG05 are used.
- 3 Use PKG03 to indicate the organization that publishes the code list being referred to.
- 4 Special marking or tagging data can be given in PKG05 (description).

Data Element Summary

<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
<u>Des.</u>	<u>Element</u>		
PKG01	349	Item Description Type Code indicating the format of a description X Semi-structured (Code and Text)	X ID 1/1
PKG02	753	Packaging Characteristic Code Code specifying the marking, packaging, loading and related characteristics being described 34 Product Marking 36 Package Specifications	O ID 1/5
PKG03	559	Agency Qualifier Code Code identifying the agency assigning the code values AS Assigned by Seller	X ID 2/2
PKG04	754	Packaging Description Code A code from an industry code list which provides specific data about the marking, packaging or loading and unloading of a product	X AN 1/7

Segment: **N1** Name
Position: 310
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: 1
Purpose: To identify a party by type of organization, name, and code
Syntax Notes: 1 At least one of N102 or N103 is required.
 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:
Comments: 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
 2 N105 and N106 further define the type of entity in N101.

Data Element Summary

Ref.	Data Element	Name	Attributes
M	N101	98 Entity Identifier Code	M ID 2/3
		Code identifying an organizational entity, a physical location, property or an individual	
		BY Buying Party (Purchaser)	
		MF Manufacturer of Goods	
		OU Outside Processor	
		A resource extraneous to primary material provider that performs additional material processing prior to delivery of the material to the primary provider's customer	
		SF Ship From	
		ST Ship To	
		SU Supplier/Manufacturer	
	N102	93 Name	X AN 1/60
		Free-form name	
	N103	66 Identification Code Qualifier	X ID 1/2
		Code designating the system/method of code structure used for Identification Code (67)	
		1 D-U-N-S Number, Dun & Bradstreet	
		91 Assigned by Seller or Seller's Agent	
	N104	67 Identification Code	X AN 2/80
		Code identifying a party or other code	

Segment: N3 Address Information
Position: 330
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: 2
Purpose: To specify the location of the named party
Syntax Notes:
Semantic Notes:
Comments:

Data Element Summary

	Ref. Des.	Data Element	Name	Attributes
M	N301	166	Address Information Address information	M AN 1/55
	N302	166	Address Information Address information	O AN 1/55

Segment: **N4 Geographic Location**
Position: 340
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: >1
Purpose: To specify the geographic place of the named party
Syntax Notes: 1 If N406 is present, then N405 is required.
Semantic Notes:
Comments: 1 A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2 N402 is required only if city name (N401) is in the U.S. or Canada.

Data Element Summary

Ref.	Data	Name	Attributes
Des.	Element		
N401	19	City Name Free-form text for city name	O AN 2/30
N402	156	State or Province Code Code (Standard State/Province) as defined by appropriate government agency	O ID 2/2
N403	116	Postal Code Code defining international postal zone code excluding punctuation and blanks (zip code for United States)	O ID 3/15

Segment: **PO1** **Baseline Item Data**

Position: 010

Loop: PO1 Mandatory

Level: Detail

Usage: Mandatory

Max Use: 1

Purpose: To specify basic and most frequently used line item data

Syntax Notes:

- 1 If PO103 is present, then PO102 is required.
- 2 If PO105 is present, then PO104 is required.
- 3 If either PO106 or PO107 is present, then the other is required.
- 4 If either PO108 or PO109 is present, then the other is required.
- 5 If either PO110 or PO111 is present, then the other is required.
- 6 If either PO112 or PO113 is present, then the other is required.
- 7 If either PO114 or PO115 is present, then the other is required.
- 8 If either PO116 or PO117 is present, then the other is required.
- 9 If either PO118 or PO119 is present, then the other is required.
- 10 If either PO120 or PO121 is present, then the other is required.
- 11 If either PO122 or PO123 is present, then the other is required.
- 12 If either PO124 or PO125 is present, then the other is required.

Semantic Notes:

Comments:

- 1 See the Data Element Dictionary for a complete list of IDs.
- 2 PO101 is the line item identification.
- 3 PO106 through PO125 provide for ten different product/service IDs per each item.
For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Data Element Summary

<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
<u>Des.</u>	<u>Element</u>		
PO101	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	O AN 1/20
PO102	330	Quantity Ordered Quantity ordered	X R 1/15
PO103	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken LB Pound	O ID 2/2
PO106	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) VO Vendor's Order Number	X ID 2/2
PO107	234	Product/Service ID Identifying number for a product or service	X AN 1/48
PO108	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) VN Vendor's (Seller's) Item Number	X ID 2/2
PO109	234	Product/Service ID Identifying number for a product or service	X AN 1/48
PO110	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) HN Heat Number	X ID 2/2
PO111	234	Product/Service ID Identifying number for a product or service	X AN 1/48
PO112	235	Product/Service ID Qualifier	X ID 2/2

			Code identifying the type/source of the descriptive number used in Product/Service ID (234)		
		GC	Grade Code		
PO113	234	Product/Service ID		X	AN 1/48
			Identifying number for a product or service		
PO116	235	Product/Service ID Qualifier		X	ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)		
		PO	Purchase Order Number		
PO117	234	Product/Service ID		X	AN 1/48
			Identifying number for a product or service		
PO118	235	Product/Service ID Qualifier		X	ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)		
		BP	Buyer's Part Number		
PO119	234	Product/Service ID		X	AN 1/48
			Identifying number for a product or service		
PO120	235	Product/Service ID Qualifier		X	ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)		
			Refer to 004010 Data Element Dictionary for acceptable code values.		
PO121	234	Product/Service ID		X	AN 1/48
			Identifying number for a product or service		
PO122	235	Product/Service ID Qualifier		X	ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)		
		KF	Item Type Number		
PO123	234	Product/Service ID		X	AN 1/48
			Identifying number for a product or service		
PO124	235	Product/Service ID Qualifier		X	ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)		
		A6	Document Identification Code		
			Item identifier subclassifies the intended use of the transaction		
PO125	234	Product/Service ID		X	AN 1/48
			Identifying number for a product or service		

Segment: **LIN** Item Identification

Position: 015

Loop: PO1 Mandatory

Level: Detail

Usage: Optional

Max Use: >1

Purpose: To specify basic item identification data

Syntax Notes:

- 1 If either LIN04 or LIN05 is present, then the other is required.
- 2 If either LIN06 or LIN07 is present, then the other is required.
- 3 If either LIN08 or LIN09 is present, then the other is required.
- 4 If either LIN10 or LIN11 is present, then the other is required.
- 5 If either LIN12 or LIN13 is present, then the other is required.
- 6 If either LIN14 or LIN15 is present, then the other is required.
- 7 If either LIN16 or LIN17 is present, then the other is required.
- 8 If either LIN18 or LIN19 is present, then the other is required.
- 9 If either LIN20 or LIN21 is present, then the other is required.
- 10 If either LIN22 or LIN23 is present, then the other is required.
- 11 If either LIN24 or LIN25 is present, then the other is required.
- 12 If either LIN26 or LIN27 is present, then the other is required.
- 13 If either LIN28 or LIN29 is present, then the other is required.
- 14 If either LIN30 or LIN31 is present, then the other is required.

Semantic Notes:

- 1 LIN01 is the line item identification

Comments:

- 1 See the Data Dictionary for a complete list of IDs.
- 2 LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>		
M	LIN02	235 Product/Service ID Qualifier	M ID 2/2
		Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
		PD Part Number Description	
M	LIN03	234 Product/Service ID	M AN 1/48
		Identifying number for a product or service	
	LIN08	235 Product/Service ID Qualifier	X ID 2/2
		Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
		SF Surface Finish	
	LIN09	234 Product/Service ID	X AN 1/48
		Identifying number for a product or service	
	LIN10	235 Product/Service ID Qualifier	X ID 2/2
		Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
		TP Product Type Code	
	LIN11	234 Product/Service ID	X AN 1/48
		Identifying number for a product or service	

Segment: **CTP Pricing Information**
Position: 040
Loop: CTP Optional
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify pricing information
Syntax Notes:

- 1 If either CTP04 or CTP05 is present, then the other is required.
- 2 If CTP06 is present, then CTP07 is required.
- 3 If CTP09 is present, then CTP02 is required.
- 4 If CTP10 is present, then CTP02 is required.
- 5 If CTP11 is present, then CTP03 is required.

Semantic Notes:

- 1 CTP07 is a multiplier factor to arrive at a final discounted price. A multiplier of .90 would be the factor if a 10% discount is given.
- 2 CTP08 is the rebate amount.

Comments:

- 1 See Figures Appendix for an example detailing the use of CTP03 and CTP04. See Figures Appendix for an example detailing the use of CTP03, CTP04 and CTP07.

Data Element Summary

<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
CTP02	236	Price Identifier Code Code identifying pricing specification CON Contract Price	X ID 3/3
CTP03	212	Unit Price Price per unit of product, service, commodity, etc.	X R 1/17
CTP10	499	Condition Value Identifies rate restrictions or provisions	O AN 1/10

Segment: **MEA** Measurements
Position: 049
Loop: PO1 Mandatory
Level: Detail
Usage: Optional
Max Use: 40
Purpose: To specify physical measurements or counts, including dimensions, tolerances, variances, and weights (See Figures Appendix for example of use of C001)
Syntax Notes:

- 1 At least one of MEA03 MEA05 MEA06 or MEA08 is required.
- 2 If MEA05 is present, then MEA04 is required.
- 3 If MEA06 is present, then MEA04 is required.
- 4 If MEA07 is present, then at least one of MEA03 MEA05 or MEA06 is required.
- 5 Only one of MEA08 or MEA03 may be present.

Semantic Notes:

- 1 MEA04 defines the unit of measure for MEA03, MEA05, and MEA06.

Comments:

- 1 When citing dimensional tolerances, any measurement requiring a sign (+ or -), or any measurement where a positive (+) value cannot be assumed, use MEA05 as the negative (-) value and MEA06 as the positive (+) value.

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
MEA01	737	Measurement Reference ID Code	O ID 2/2
		Code identifying the broad category to which a measurement applies	
		DT Dimensional Tolerance	
		PD Physical Dimensions	
		WT Weights	
MEA02	738	Measurement Qualifier	O ID 1/3
		Code identifying a specific product or process characteristic to which a measurement applies	
		ID Inside Diameter	
		LN Length	
		OD Outside Diameter	
		TH Thickness	
		WD Width	
		WT Weight	
MEA03	739	Measurement Value	X R 1/20
		The value of the measurement	
MEA04	C001	Composite Unit of Measure	X
		To identify a composite unit of measure (See Figures Appendix for examples of use)	
M	C00101	Unit or Basis for Measurement Code	M ID 2/2
		Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
		ED Inches, Decimal--Nominal	
		EM Inches, Decimal-Minimum	
		IN Inch	
		KG Kilogram	
		LB Pound	
		LF Linear Foot	
		MB Millimeter-Nominal	
		MM Millimeter	
		MZ Millimeter-minimum	
MEA05	740	Range Minimum	X R 1/20
		The value specifying the minimum of the measurement range	

MEA06

741

Range Maximum

X R 1/20

The value specifying the maximum of the measurement range

Segment: **PID** Product/Item Description

Position: 050

Loop: PID Optional

Level: Detail

Usage: Optional

Max Use: 1

Purpose: To describe a product or process in coded or free-form format

Syntax Notes:

- 1 If PID04 is present, then PID03 is required.
- 2 At least one of PID04 or PID05 is required.
- 3 If PID07 is present, then PID03 is required.
- 4 If PID08 is present, then PID04 is required.
- 5 If PID09 is present, then PID05 is required.

Semantic Notes:

- 1 Use PID03 to indicate the organization that publishes the code list being referred to.
- 2 PID04 should be used for industry-specific product description codes.
- 3 PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
- 4 PID09 is used to identify the language being used in PID05.

Comments:

- 1 If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
- 2 Use PID06 when necessary to refer to the product surface or layer being described in the segment.
- 3 PID07 specifies the individual code list of the agency specified in PID03.

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	PID01	349 Item Description Type Code indicating the format of a description F Free-form S Structured (From Industry Code List)	M ID 1/1
	PID03	559 Agency Qualifier Code Code identifying the agency assigning the code values ST American Iron & Steel Institute	X ID 2/2
	PID04	751 Product Description Code A code from an industry code list which provides specific data about a product characteristic	X AN 1/12
	PID05	352 Description A free-form description to clarify the related data elements and their content	X AN 1/80
	PID07	822 Source Subqualifier A reference that indicates the table or text maintained by the Source Qualifier	O AN 1/15

Segment: **REF** Reference Identification
Position: 100
Loop: PO1 Mandatory
Level: Detail
Usage: Optional
Max Use: >1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification RV Receiving Number SE Serial Number	M ID 2/3
	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X AN 1/30

Segment: **DTM** **Date/Time Reference**
Position: 210
Loop: PO1 Mandatory
Level: Detail
Usage: Optional
Max Use: 10
Purpose: To specify pertinent dates and times
Syntax Notes:

- 1 At least one of DTM02 DTM03 or DTM05 is required.
- 2 If DTM04 is present, then DTM03 is required.
- 3 If either DTM05 or DTM06 is present, then the other is required.

Semantic Notes:
Comments:

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
M	DTM01	374	Date/Time Qualifier Code specifying type of date or time, or both date and time 007 Effective	M ID 3/3
	DTM02	373	Date Date expressed as CCYYMMDD	X DT 8/8
	DTM03	337	Time Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	X TM 4/8
	DTM04	623	Time Code Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow Refer to 004010 Data Element Dictionary for acceptable code values.	O ID 2/2
	DTM05	1250	Date Time Period Format Qualifier Code indicating the date format, time format, or date and time format Refer to 004010 Data Element Dictionary for acceptable code values.	X ID 2/3
	DTM06	1251	Date Time Period Expression of a date, a time, or range of dates, times or dates and times	X AN 1/35

Segment: **SCH** Line Item Schedule
Position: 295
Loop: SCH Optional
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify the data for scheduling a specific line-item
Syntax Notes:

- 1 If SCH03 is present, then SCH04 is required.
- 2 If SCH08 is present, then at least one of SCH09 or SCH10 is required.
- 3 If SCH09 is present, then SCH08 is required.
- 4 If SCH10 is present, then SCH08 is required.

Semantic Notes:

- 1 SCH12 is the schedule identification.

Comments:

- 1 SCH05 specifies the interpretation to be used for SCH06 and SCH07.

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	SCH01	380	Quantity Numeric value of quantity	M R 1/15
M	SCH02	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken LB Pound	M ID 2/2
M	SCH05	374	Date/Time Qualifier Code specifying type of date or time, or both date and time 077 Requested for Delivery (Week of)	M ID 3/3
M	SCH06	373	Date Date expressed as CCYYMMDD	M DT 8/8

Segment: **CTT** Transaction Totals
Position: 010
Loop: CTT Optional
Level: Summary
Usage: Optional
Max Use: 1
Purpose: To transmit a hash total for a specific element in the transaction set
Syntax Notes: 1 If either CTT03 or CTT04 is present, then the other is required.
 2 If either CTT05 or CTT06 is present, then the other is required.
Semantic Notes:
Comments: 1 This segment is intended to provide hash totals to validate transaction completeness and correctness.

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	CTT01	354	Number of Line Items Total number of line items in the transaction set	M N0 1/6

Segment: **SE** Transaction Set Trailer
Position: 030
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Syntax Notes:

Semantic Notes:

Comments: 1 SE is the last segment of each transaction set.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	SE01	96	Number of Included Segments Total number of segments included in a transaction set including ST and SE segments	M N0 1/10
M	SE02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9